

# Direct Wire-in Photo Controls With Fixed or Swivel Mounting

Suitable for wet locations

- High impact polycarbonate housing.
- Turn on between 1 and 5 foot candles.
- Turn on / turn off ratio: 1:5.
- Single-pole, single-throw switching.
- Minimum time delay: 15 seconds.
- Contact position at night normally closed.
- External slide clip allows light level adjustment.
- With ½" -14 threaded stem. Fits ½" knockout.
- With 6" color-coded lead wire.
- Temperature range: -40°F (-40°C) to 149°F (65°C).



## Durable Construction

Durable polycarbonate housing with ½" threaded stem easily mounts to a standard weatherproof box with a ½" outlet. Ideal for wall packs and other types of security and area lighting. All controls come with locknut, rubber gasket and easy-to-read instructions.

## Positive Snap Action Switch

A dependable bi-metal switch provides positive on/off switching. Built-in time delay prevents accidental turn off that may result from stray automobile headlights, lightning flashes or any momentary brightness. Switch contacts are normally closed and, should they fail, remain in an ON position.

Catalog No.	Base	Voltage	Tungsten (watts)	Ballast (volt amps)	Carton Quantity	Weight per 100 units
<b>30825</b>	Fixed	120	2000	1900	10	30 lbs.
<b>30830</b>	Fixed	208-277	2000	1900	10	30 lbs.
<b>30832*</b>	Fixed	480	2000	1900	10	30 lbs.
<b>30847*</b>	Fixed	120	3000	2900	10	40 lbs.
<b>30826</b>	Swivel	120	2000	1900	10	30 lbs.

\*All of the above items are both UL Listed and CSA Approved, except Catalog Nos. 30847 and 30832.

**NOTE: See Basic Wiring Diagram on the following page.**